

80W~90W SINGLE OUTPUT AC/DC ADAPTOR

Features

- Universal input 100 to 240VAC
- Meets FCC/CISPR/VCCI class B EMI
- Low profile and low cost
- High efficiency
- IEC320 inlet class I or class II
- Compact size: L133*W57*H30 mm
- OVP, OPP auto recovery



Specifications

INPUT

Voltage range	100-240V
Frequency	47-63Hz
Inrush current	30A@100VAC full load, cold start 60A@240VAC full load, cold start
Fusing	On board

OUTPUT

Power rating	80/90W
Line regulation	± 1% all outputs
Load regulation	5%
Ripple and noise	2% max all outputs
Hold-up time	10mS
Overvoltage protection	Main rate 30%
Efficiency	80% min.

ENVIRONMENTAL

Operating temperature	0°C to 40°C
Storage temperature	-20°C to +85°C
Coolong	Free air convection
Temperature coefficient	± 0.03%/°C
Humidity	5%~95% RH non-condensing

GENERAL

MTBF	30,000 hours Min
Dimensions (LxWxH)	L133*W57*H30 mm
Weight	420g
Multi-plug output connector	Please see right side pic.

STANDARDS

Safety standards	Approved to UL/CUL, TUV,CCC,CB. Meets UL1950, CSA C22.2, EN60950
EMI	Meets FCC/VDE level B.
CE mark	Yes.

MODEL	O/P SINGLE
F10903-A(XX) 3P	19V/4.75A 90W MAX
F10903-A(XX) 3P	20V/4.5A 90W MAX
F10903-D(XX) 3P	24V/3.75A 90W MAX
F10903-C(XX) 3P	12V/6.66A 80W MAX

