



6.65KG/M

SPECIFICATIONS:

MODEL	OUTPUT POWER	BRIDGE POWER	T.H.D	FREQUENCY	SEPARATION	SIN	INPUT	WEIGHT	SIZE
	@14.4V (rms)	@14.4V (rms)		RESPONSE			SENSITIVITY		W×D×H(MM)
TWB704	4×70W @ 4Ω 4×100W @ 2Ω	2×200W @ 4Ω	<0.10%	10Hz-30KHz	>56dB	>90dB	0.2-5V	2.8	53x170x260
TWB1004	4×100W @ 4Ω 4×150W @ 2Ω	2×300W @ 4Ω	<0.10%	10Hz-30KHz	>56dB	>90dB	0.2-5V		53x170x320
TWB1000D	1×1000W @ 1Ω		<1.0%	16-200Hz	NA	>98dB	0.2-5V		53x170x280
TWB1200D	1×1200W @ 1Ω		<1.0%	16-200Hz	NA	>98dB	0.2-5V		53x170x300
TWB1500D	1×1500W @ 1Ω		<1.0%	16-200Hz	NA	(Minimum Gain)>10	0.2-5V		53x170x260
TWB2000D	1×2000W @ 1Ω		<1.0%	16-200Hz	NA	(Minimum Gain)>10	0.2-5V		53x170x320