



SPECIFICATIONS:

MODEL	OUTPUT POWER	BRIDGE POWER	T.H.D	FREQUENCY	SEPARATION	SIN	INPUT	WEIGHT	SIZE
	@14.4V (rms)	@14.4V (rms)		RESPONSE			SENSITIVITY		W×D×H(MM)
TWH502	2x50W @ 4 2x75W @ 2	1x150W @ 4	<0.10%	10Hz-30KHz	>56dB	>90dB	0.2-5V		240
TWH602	2x60W @ 4 2x90W @ 2	1x180W @ 4	<0.10%	10Hz-30KHz	>56dB	>90dB	0.2-5V		220
TWH404	4x40W @ 4	2x120W @ 4	<0.10%	10Hz-30KHz	>56dB	>90dB	0.2-5V		280
	4x60W @ 2								
TWH604	4x50W @ 4 4x75W @ 2	2x150W @ 4	<0.10%	10Hz-30KHz	>56dB	>90dB	0.2-5V		300
TWH854	4x85W @ 4	2x260W @ 4	<0.10%	10Hz-30KHz	>56dB	>90dB	0.2-5V		340
	4x130W @ 2								
TWH350D			<1.0%	16-200Hz	NA	>98dB	0.2-5V		180
	1x350W @ 1								
TWH500D			<1.0%	16-200Hz					280
	1x500W @ 1								
TWH1000D			<1.0%	16-200Hz					320
	1x1000W @ 1								
TWH1500D			<1.0%	16-200Hz					350
	1x1500W @ 1								