

2-way Hi-quality component

- 6.5 Carbon Fiber cone woofer with
- 200W peak power(100W RMS)
- 150OZ magnet
- SPL 90dB M/W
- 1" Titanium Dome tweeter Neo magnet
- Frequency 65-20KHz
- Two-way crossover 12db/oct.(3.8KHZ)



WS-C65CB

2-way Hi-quality component

- 6.5 Paper cone woofer
- 150W peak power(75W RMS)
- 130OZ magnet
- SPL 90dB M/W
- 1" Silk Dome tweeter Neo magnet
- Frequency 65-20KHz
- Two-way crossover 6db/oct.(3.8KHZ)



WS-C65D



WS-102W

Specification :

- 10" NonPressed Paper Cone Subwoofer
- 600Watts Peak Power(300Watts RMS)
- Dual 2"4 Ω Impedance ASV Voice Coil
- Frequency Response: 30Hz-1500Hz
- 50 Oz Magnet
- SPL 86dB M/W

WS-102WS

Specification :

- 10" NonPressed Paper Cone Subwoofer
- 800Watts Peak Power(400Watts RMS)
- Dual 2"4 Ω Impedance ASV Voice Coil
- Frequency Response: 30Hz-1500Hz
- 100 Oz Magnet
- SPL 88dB M/W



WS-122W

Specification :

- 12" NonPressed Paper Cone Subwoofer
- 1000Watts Peak Power(500Watts RMS)
- Dual 2.6"4 Ω Impedance ASV Voice Coil
- Frequency Response: 30Hz-1500Hz
- 60 Oz Magnet
- SPL 86dB M/W

WS-122WS

Specification :

- 12" NonPressed Paper Cone Subwoofer
- 1200Watts Peak Power(600Watts RMS)
- Dual 2.6"4 Ω Impedance ASV Voice Coil
- Frequency Response: 30Hz-1500Hz
- 120 Oz Magnet
- SPL 88dB M/W



Specification :

Frequency	65-20kHz
Sensitivity	89dB/W/M
Max Power	120W
Magnet	10oz
Voice Coil	25mm
Woofer	Injection Cone
Midrange and Tweeter	30mm Mylar Dome Tweeter

WS-652P

Specification :

Frequency	65-20kHz
Sensitivity	89dB/W/M
Max Power	120W
Magnet	20oz
Voice Coil	25mm
Woofer	Injection Cone
Midrange and Tweeter	50mm Mylar Dome Tweeter and 30mm Piezo Tweeter



WS-693P